

CHARGEURS & MAINTENEURS

GAMME SPX



SPX457 1A



SPX458 3A



SPX459 6A



SPX460 10A

i INFORMATIONS TECHNIQUES

| MODELE | SPX 457 | SPX 458 | SPX 459 | SPX 460 |
|--------------------------------|---|-----------------|-----------------|-----------------|
| REFERENCE | 94065457* | 94065458* | 94065459* | 94065460* |
| | * La lettre indique le type de prise PRISE EU = C | | PRISE UK = G | PRISE AU = I |
| Voltage (DC) | 6/12 V | 12 V | 12 V | 12 V |
| Nominal AC voltage | 230V AC - 50 Hz | | | |
| Courant de charge Max. | 1 A | 3 A | 6 A | 10 A |
| Indice de protection IP | IP 66 | IP 54 | / | / |
| Type de batteries | Plomb & Lithium | Plomb & Lithium | Plomb & Lithium | Plomb & Lithium |
| Taille du câble(cm) | 191 | 191 | 195 | 195 |
| Températures max d'utilisation | -20° to +50° C | | | |

12V6A

Fourni avec pinces crocodiles et œillets de connexion.



Attache format cintre

Tout-automatique et arrêt de sécurité.

Protections anti-dérappantes

